

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
3 June 2004 (03.06.2004)


PCT

(10) International Publication Number
WO 2004/045428 A1

- (51) International Patent Classification⁷: **A61B 17/32**
- (21) International Application Number:
PCT/ZA2003/000126
- (22) International Filing Date:
1 September 2003 (01.09.2003)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
2002/9334 18 November 2002 (18.11.2002) ZA
2003/5355 11 July 2003 (11.07.2003) ZA
- (71) Applicant and
(72) Inventor: **MILTON, Trevor, John** [ZA/ZA]; 19A North
Road, Dunkeld West, Johannesburg, Gauteng Province,
2196 South Africa (ZA).
- (72) Inventor: **HOLMAN, Robert, Gerard**; 6 Lakewood
Lane, Cedar Lake, Morobeladal Ext 8, Sandton, Gauteng
Province, 2196 South Africa (ZA).
- (74) Agent: **PILKINGTON, Donovan**; Institute of Inventors
and Innovators, P.O. Box 286, 2132 Saxonwold (ZA).
- (81) Designated States (*national*): AE, AG, AL, AM, AT, AU,
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,
CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH,
GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC,
LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW,
MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC,
SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA,
UG, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (*regional*): ARIPO patent (GH, GM,
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,
ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO,

[Continued on next page]

(54) Title: DISPOSABLE SCALPEL WITH RETRACTABLE BLADE



(57) Abstract: A scalpel is provided having a handle (1) with a longitudinally extending cavity (3) therein, a blade carrier (2) within the cavity and movable longitudinally relative to the handle between an operative position in which a blade carried thereby is exposed for use at an open end (8) of the cavity and an inoperative position in which a blade carried thereby is retracted within the cavity in the handle, and a manually operable slider (4) associated with the blade carrier and passing through a slot (6) in a wall of the handle at an edge (7) thereof, herein termed the top edge. The handle is moulded as a single piece moulding with an integral bridge (10) defining an endless open end (11) to the cavity through which the blade carrier is introduced into the cavity. The slider is formed as a separate part that snap fits to the blade carrier after its introduction through the open end of the cavity to form a blade carrier and slider assembly. "Click stops" are provided in the operative and inoperative positions by tooth (19, 20) and notch (23) formations on the slider and slot. A final innermost permanently locked position is also preferably provided.

WO 2004/045428 A1



SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

— *with international search report*

DISPOSABLE SCALPEL WITH RETRACTABLE BLADE

5 FIELD OF THE INVENTION

This invention relates to a disposable scalpel having a retractable blade and, more particularly, to a disposable scalpel in which movement of the blade relative to a supporting scalpel handle between an extended operative
10 position and a retracted inoperative position is achieved by moving a blade carrier by way of a thumb operable slider attached, generally by way of a slot through the wall of the handle, to the blade carrier.

BACKGROUND TO THE INVENTION

15

Disposable scalpels having retractable blades have been proposed and produced in many different forms. The various different forms can, for present purposes, be considered to fall into two different categories; a first being scalpels in which the thumb operable slider projects through a side wall
20 of the scalpel handle, and a second in which the slider projects through a slot in one edge that can be considered to be the top edge of the scalpel handle.

The first type of scalpel that has the slider projecting through a side wall of
25 the handle is considered to suffer from a number of disadvantages, not least of which is that one designed for use by a right-handed person cannot easily be used by a left-handed person and vice versa. United States patent No 6,254,621 describes a scalpel that is typical of this type.

30 The second type of scalpel that has the slider projecting through the top edge of the scalpel handle generally has the disadvantage that the scalpel handle is made in two parts that are subsequently secured together with the blade

carrier inside the handle and the associated slider projecting through a slot in the top edge of the composite handle. Typical of this type of construction are the scalpels described in United States patents 5,330,493; 5,556,409; and 5,571,127. The two-part construction of the handle is considered by
5 applicant to be undesirable for a variety of reasons not least of which is the fact that the handle could possibly come apart.

There are a number of factors that are independent of the type of construction that are considered to be desirable and that are present to
10 greater or lesser extents in existing scalpels, these being factors that contribute to the scalpel blade being held firmly in its operative position; being held positively in its retracted inoperative position; and also a facility aimed at preventing reuse of a scalpel in an effort to avoid so-called sharps injuries to personnel that may come into contact with used medical
15 equipment.

OBJECT OF THE INVENTION

It is, accordingly, an object of this invention to provide a scalpel with a
20 retractable blade that has one or more improved features over the prior art scalpels of which applicant is aware.

SUMMARY OF THE INVENTION

25 In accordance with this invention there is provided a scalpel having a handle with a longitudinally extending cavity therein, a blade carrier within the cavity and movable longitudinally relative to the handle between an operative position in which a blade carried thereby is exposed for use at an open end of the cavity and an inoperative position in which a blade carried thereby is
30 retracted within the cavity in the handle, and a manually operable slider associated with the blade carrier and passing through a slot in a wall of the handle at an edge thereof, herein termed the top edge: the scalpel being

characterized in that the handle is moulded as a single piece moulding with an integral bridge defining an endless open end to the cavity through which the blade carrier may be introduced into the cavity and in that the slider is formed as a separate part that snap fits to the blade carrier after introduction
5 through the open end of the cavity to form a blade carrier and slider assembly.

Further features of the invention provide for the slider and one or other longitudinally extending edge of the slot to be provided with co-operating
10 tooth and notch formations that cooperate to releasably hold the blade carrier and slider assembly in "click-stop" manner in the operative and inoperative positions; for the blade carrier and slider assembly to have an innermost, terminal locked position defined by co-operating formations on the slider and edges of the slot, such terminal locked position being one in which the blade
15 carrier is located inwards of the normal inoperative position and from which it is substantially impossible to unlock the blade carrier, at least for practical purposes; for a plurality of notches to be associated with both the operative and inoperative positions of the blade carrier and slider assembly so that a series of at least two and optionally three or more "click-stops" are
20 associated with each of the operative and inoperative positions such that a person operating the scalpel will know exactly, by feel, and optionally also hearing, the position of the blade carrier in the handle; and for the tooth and notch formations to be adapted such that an audible "click" is created when a tooth engages a notch.

25

A further feature of the invention provides for the slider to have a pair of transverse tongues with oppositely directed latch formations at their inner ends for cooperating with cooperant transverse sockets formed in the blade carrier. The tongues are preferably coplanar and spaced apart in the
30 longitudinal direction of the slider.

Preferably, the blade carrier is configured such that it can accept a plurality of different style blades, thereby rendering it more versatile than prior art scalpels.

- 5 In order that the invention may be more fully understood one embodiment thereof will now be described with reference to the accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

10 In the drawings:-

- Figure 1 is an exploded perspective view from the side of a scalpel according to the invention but offset such that the top edge of the handle is somewhat visible;
- 15 Figure 2 is a similar view, but more from the top, and showing the scalpel partly assembled;
- Figure 3 is a cross-section taken through the handle of the scalpel;
- 20 Figure 4 is an inverted plan view of the slider showing the tooth and slide block formations formed integral therewith;
- Figure 5 is a detail of the slider in its exploded position relative to the carrier and as illustrated in Figure 2;
- 25 Figure 6 is a detail, partly broken away, and showing the cooperation between tooth and notch formations of the slot and slider with the latter in the operative position;
- 30 Figure 7 is a perspective view of the scalpel from one side of the top thereof showing the slider partly broken away in its fully locked position;

Figure 8 is a view similar to Figure 6 showing the cooperation between tooth and notch formations of the slot and slider with the latter in the inoperative position; and,

Figure 9 is a detail similar to Figure 8 but showing the tooth and notch formations in the final locked position of the slider relative to the scalpel handle (in the position illustrated in Figure 7).

DETAILED DESCRIPTION WITH REFERENCE TO THE DRAWINGS

In the embodiment of the invention illustrated in the drawings, a scalpel comprises a single piece injection moulded plastics handle (1), a blade carrier (2) slidable longitudinally in a longitudinal cavity (3) within the plastics handle, a separately moulded, manually operable slider (4) that combines with the blade carrier to form a blade carrier assembly in the assembled condition, and, for use, a scalpel blade (5) that is fitted to the blade carrier.

The handle has a longitudinally extending slot (6) extending along its operatively top edge (7) from a forward end (8) of the handle towards a rear end (9) thereof and communicating with the cavity inside. An integral bridge (10) at the front end of the top edge forms an endless open end (11) to the cavity and provides dimensional stability to this end for firmly holding the blade carrier in its operative position.

The blade carrier is elongate and has a longitudinally extending ridge (12) that is received in a cooperating groove (13) (see Figure 3) on one side wall of the cavity. The blade carrier is configured to slide longitudinally within the cavity and to receive and support a variety of different scalpel blade types. The blade carrier is clearly shaped, in cross-section, to be introduced through the open end (11) to the cavity.

The blade carrier also has a pair of transverse sockets (14) being configured to receive a pair of transverse tongues (15) extending from the slider, the tongues each having a catch formation (16) at its free end that locks onto the blade carrier in irreversible manner when the tongues are introduced into the sockets with the blade carrier in the cavity. Once this has been achieved, the blade carrier is held captive within the cavity and can be slid forwards and rearwards by manually operating the slider, generally by a person holding the scalpel handle and utilizing the thumb to achieve this.

10

The slider has, on its upper surface, a longitudinally extending ridge (17) that cooperates with the slot to align the slider correctly relative to it. Extending laterally outwards from the ridge at each end thereof is an integral miniature slide block (18) that cooperates with the one edge of the slot and, on the other side of the ridge, are a forward tooth (19) positioned inwards from the nearer end of the ridge and a rearward tooth (20) located opposite the rear slide block (18).

The teeth (19) and (20) are substantially identical and are of trapezoidal or triangular shape to provide inclined faces (21) to cooperate with the inclined edges (22) to notches (23) formed in the associated edge of the slot at both the front and rear ends thereof. In the case of both the front and rear ends of the slot there are provided a series of four juxtaposed notches for cooperation with the forward tooth (19) and rearward tooth (20) respectively when the slider is at the forward or rear ends of the slot.

The arrangement is such that as the slider is moved towards either of the operative or inoperative positions the respective tooth will engage sequentially with the notches of the series of four and will form a "click-stop" in each position. A person operating the slider will be able to feel these sequential "click-stops" and, with appropriate design, also hear them. It will

thus be immediately apparent as to the exact location of the blade relative to the handle.

5 In addition to the above, the rear end of the slot is also provided with a ramp (24) on the side opposite the notches, the ramp communicating with a neck (25) that in turn communicates with a rectangular terminal aperture (26) forming the inner end of the slot. This arrangement is such that when additional force is applied to the slider in a direction towards the rear end of the handle, the slide block (18) and opposite rear tooth (20) are forced
10 together through the neck and into the aperture in an irreversible manner so that the slider is permanently locked in the retracted position. This final position is illustrated clearly in Figure 9.

15 It will be understood that, in use, the scalpel may be stored and transported with the blade carrier and associated blade in a retracted position with the slider held in one of the "click-stop" retracted positions. This position may also be used during the conduct of operations in between times when the scalpel is required for use. As and when required, the blade carrier can be moved to present the scalpel blade in its operative position with the blade
20 carrier being arrested in a forward "click-stop" position. The position of the blade relative to the handle can be sensed extremely easily by a person using the scalpel. It is also to be noted that the different "click-stop" positions can be used for the purpose of depth control

25 Once the scalpel has served its purpose and is to be disposed of, the slider is moved to its final locked position so that, to all intents and purposes, it is impossible to use the scalpel again. The scalpel blade is thus held in an extremely safe locked inoperative position for disposal, thereby avoiding the possibility of any so-called sharps injuries.

It will be understood that numerous variations may be made to the embodiment of the invention described above without departing from the scope hereof.

5

10

15

20

25

30

CLAIMS:

1. A scalpel having a handle (1) with a longitudinally extending cavity (3) therein, a blade carrier (2) within the cavity and movable longitudinally relative to the handle between an operative position in which a blade carried thereby is exposed for use at an open end (8) of the cavity and an inoperative position in which a blade carried thereby is retracted within the cavity in the handle, and a manually operable slider (4) associated with the blade carrier and passing through a slot (6) in a wall of the handle at an edge (7) thereof, herein termed the top edge; the scalpel being characterized in that the handle is moulded as a single piece moulding with an integral bridge (10) defining an endless open end (11) to the cavity through which the blade carrier may be introduced into the cavity and in that the slider is formed as a separate part that snap fits to the blade carrier after introduction through the open end of the cavity to form a blade carrier and slider assembly.
2. A scalpel as claimed in claim 1 in which the slider and at least one longitudinally extending edge of the slot are provided with co-operating tooth (19, 20) and notch (23) is formations that cooperate to releasably hold the blade carrier and slider assembly in "click-stop" manner in the operative and inoperative positions.
3. A scalpel as claimed in either one of claims 1 or 2 in which for the blade carrier and slider assembly have an innermost, terminal locked position defined by co-operating formations (25, 18, 20) on the slider and edges of the slot, such terminal locked position being one in which the blade carrier is located inwards of the normal inoperative position and from which it is substantially impossible to unlock the blade carrier, at least for practical purposes.

4. A scalpel as claimed in claim 2 in which a plurality of notches are associated with both the operative and inoperative positions of the blade carrier and slider assembly so that a series of at least two, and optionally three or more "click-stops" are associated with each of the operative and inoperative positions.
5. A scalpel as claimed in either one of claims 2 or 4 in which the "click-stops" are configured to create an audible sound upon engagement of a tooth with a notch.
6. A scalpel as claimed in any one of the preceding claims in which the slider has a pair of transverse tongues (15) with oppositely directed catch formations (16) at their inner ends for cooperating with cooperant transverse sockets (14) formed in the blade carrier.
7. A scalpel as claimed in claim 6 in which the tongues are coplanar and spaced apart in the longitudinal direction of the slider.
8. A scalpel as claimed in any one of the preceding claims in which the blade carrier is configured such that it can accept a plurality of different style blades.

FIG 1





FIG 2









FIG 7




FIG 8





FIG 9



INTERNATIONAL SEARCH REPORT

International Application No

PCT/ZA 03/00126

A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 A61B17/32

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 A61B B26B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 6 391 041 B1 (EDENS ROGER A) 21 May 2002 (2002-05-21)	1,2,5,8
Y	column 3, line 8 - line 14 ----	3,4
Y	US 6 254 621 B1 (GRATTON JOHN P ET AL) 3 July 2001 (2001-07-03)	3,4
	column 3, line 53 -column 4, line 42 ----	
A	US 5 599 351 A (HABER TERRY M ET AL) 4 February 1997 (1997-02-04)	1
	column 2, line 46 -column 3, line 45 ----	
A	US 5 431 672 A (COTE DANA M ET AL) 11 July 1995 (1995-07-11)	1
	column 4, line 30 - line 38 -----	

☐ Further documents are listed in the continuation of box C.☒ Patent family members are listed in annex.

* Special categories of cited documents:

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

- *T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- *X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- *Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- * & * document member of the same patent family

Date of the actual completion of the international search

19 December 2003

Date of mailing of the international search report

16/01/2004

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Angeli, M

INTERNATIONAL SEARCH REPORT

International Application No

PCT/ZA 03/00126

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
US 6391041	B1	21-05-2002	US 6503262 B1	07-01-2003
US 6254621	B1	03-07-2001	AU 7499901 A	11-12-2001
			EP 1289435 A2	12-03-2003
			WO 0191649 A2	06-12-2001
US 5599351	A	04-02-1997	NONE	
US 5431672	A	11-07-1995	CA 2147452 A1	10-11-1995
			DE 69519761 D1	08-02-2001
			DE 69519761 T2	07-06-2001
			EP 0681812 A1	15-11-1995
			JP 2608695 B2	07-05-1997
			JP 7299076 A	14-11-1995